

# सेन्टर फॉर मेटिरियल्स फॉर इलेक्टॉनिक्स टेक्नोलाजी (सी-मेट)

# CENTRE FOR MATERIALS FOR ELECTRONICS TECHNOLOGY (C-MET)

(Scientific Society, Ministry of Electronics and Information Technology (Meity), Govt. of India)

IDA PHASE – III, CHERLAPALLY, HCL (PO), HYDERABAD – 500 051

Phone: +91-40-27265587, 27267006 Fax: +91-40-27261658 Web: www.cmet.gov.in

## **ENQUIRY LETTER**

ENQ. NO.: HD/PUR/SP-39/MCM/10/2019-20/11469

Date: 13.12.2019

Subject:

Procurement of 'Multipass Calendaring Machine' - Regarding

DATE OF OPENING OF TECHNICAL BID	07	01	2020	TIME BY:12.00 hours
Due date/CLOSING for receipt of the quotations	06	01	2020	TIME BY:15.30 hours

Sir,

Sealed quotations conforming to the specifications are invited for the following item(s). Quotation may please be submitted, keeping in view, the terms and conditions given below and overleaf, otherwise quotations will be rejected.

S. No.	Description of the item	Quantity	Specifications
01	Multipass Calendaring Machine	1 no.	As per 'Annexure – I'
			enclosed

## **Terms & Conditions:**

C-MET is registered under Department of Scientific and Industrial Research (DSIR) and eligible for concessional GST rates @ 5% for Research Institutions as per Notification No. 45/2017- Central Tax (Rate) dated 14.11.2017 and Notification No. 10/2018-Integrated Tax (Rate) dated 25.01.2018. The requisite certificate for availing concessional GST Rate along with documents will be provided.

## Note:

- (i) The envelope super-scribed with [a] Quotation No. [b] Due Date & [c] Description of the Item and be sent to the undersigned before the due date.
- (ii) The quotation should be submitted in the enclosed format only.
- (iii) The Enquiry Letter No. & date should be clearly indicated in the quotation, otherwise quotation will be rejected.
- (iv) The Technical & Financial bids should be in separate sealed covers. Combined quotations will be REJECTED.
- (v) Firms or their authorized representatives are requested to attend the opening of <u>Combined/Technical bids</u> on 07.01.2020 at 12:00 hours. If there is any delay in opening of technical bids will be intimated to all bidders.
- (vi) These details are also available in our website: http://www.cmet.gov.in & CPPP Portal

Thanking you,

Yours faithfully,

(G.K.VENKATESAN) Administrative Officer

venkatesan@cmet.gov.in

Encl.: As above.

### Specific terms and conditions to the tender:-

- 1. Please submit the Technical Details/Catalogue/Data Sheets.
- 2. The offer should be valid for a period of 90 days from the date of opening of Tender.
- 3. Please send the quotations ONLY in 'SEALED COVER' indicating our tender enquiry No. and due date by Hand/speed post/courier so as to reach us on or before the due date & time. C-MET will not be responsible for any postal delays.
- 4. E-Mail/fax quotations 'WILL NOT BE ACCEPTED'.
- 5. All Tax invoices shall invariably bear your GST Registration No. (GSTIN) and the applicable GST rates. In the absence of which, the invoice(s) shall not be processed for payment.
- 6. Our standard delivery term is FOR, C-MET. In case any vendor offers delivery term of Ex-works, Packing and Forwarding charges if any should be indicated separately either as a percentage of the quoted rate or as a Lumpsum amount.
- 7. **PAYMENT OF GST/IGST**: C-MET is registered under Department of Scientific and Industrial Research (DSIR) and eligible for concessional GST rates @ 5% for Research Institutions as per Notification No. 45/2017- Central Tax (Rate) AND 47/2017 IT(Rate) both dated 14.11.2017. The requisite certificate for availing concessional IGST/GST Rate along with documents will be provided. **PAYMENT OF CUSTOM DUTY:** We are ELIGIBLE for concessional custom duty @ 5.15% as per DSIR issued certificate in terms of **Notification No. No. 51/96-Customs dated 23.07.1996** and necessary exemption certificate shall be issued upon request.
- 8. Our standard payment term is 100% within 30 days for indigenous orders and sight draft for foreign orders. Firm should provide Bank details for RTGS remittance.
- 9. **Liquidated Damages:** The delivery period quoted should be realistic. The delivery period so quoted and mentioned in the order is the essence of the order/contract. In case of delay in delivery of material as per the delivery schedule, Liquidated Damage @ 0.5% per week or part thereof on the undelivered portion subject to a maximum of 10% of the contract value shall be levied. Wherever, installation and commissioning is also involved, the supply will be deemed to have been completed only when the entire stores is supplied, installed and accepted.
- 10. **Security Deposit:** Wherever the offer value is Rs. 5.00 lakhs or above, the successful tenderer should submit Security Deposit@10% of the order value by way of Bank Guarantee /FC Receipt. The Bank Guarantee shall be obtained from any Scheduled Bank on Rs. 200/- Non Judicial Stamp paper and should be valid beyond 2 months from the completion of all contractual obligations.

Note: Clause NO. 9 & 10 are mandatory and offers of the vendors who have not agreed for the above conditions will be excluded from the procurement process. Micro and Small Vendors are not exempted from the submission of Security Deposit.

- 11. In order to avail of the benefits extended to by Govt. of India to the Micro and Small Sectors, please submit attested copy of the valid Entrepreneur Memorandum Part-II signed by the General Manager, District Industries Centre/ Udyog Adhar / NSIC Registration Certification along with your offer.
- 12. If any bidder submits forged / false document along with the tender, offer of such vendors will be summarily rejected and such bidders will be blacklisted for all future tenders.
- 13. Wherever samples are required to be submitted along with the quotation, offer without sample will not be considered.
- 14. **Price Reasonability Certificate:** Prescribed form enclosed.
- 15. **Manufacturer's authorization letter**: A copy of **manufacturer's authorization letter** for participating in the bid should be attached.

NOTE: Bidder should sign on each of the page as read and accepted thereof with signature and official stamp of the firm.

Ver fat M Administrative Officer C-MET, Hyderabad

# **CHECK LIST**

# Documents to be submitted along with the bids

S No	Description	Yes/No	Page No
1	Covering/introduction letter from the Firm referring to C-MET's tender enquiry No and date towards participation in the tender		
2	Acceptance of terms & conditions of tender enquiry		
3	Signed copy of tender enquiry		
4	Price Reasonability Certificate		
5	Bid form and Price schedule with commercial terms		
6	Manufacturer's Authorization letter		
7	Previous experience details alongwith documents like PO/WO etc. (not more than 3 years old)	NA	
8	Undertaking and declaration		
9	Technical compliance statement with/without deviation		
10	Technical brochure of the Product offered or drawings		
11	GST Registration certificate or No		
12	Bank details for NEFT/RTGS		
13	Warranty and additional warranty		



# सेन्टर फॉर मेटिरियल्स फॉर इलेक्टॉनिक्स टेक्नोलाजी (सी-मेट)

## CENTRE FOR MATERIALS FOR ELECTRONICS TECHNOLOGY (C-MET)

(Scientific Society, Ministry of Electronics and Information Technology (Meity), Govt. of India)

IDA PHASE – III, CHERLAPALLY, HCL (PO), HYDERABAD – 500 051

Phone: +91-40-27265587, 27267006 Fax: +91-40-27261658 Web: www.cmet.gov.in

## Annexure ~ I

## TECHNICAL SPECIFICATIONS FOR "MULTIPASS CALENDARING MACHINE"

C-MET requires Multipass Calendaring Machine for the purpose of the fabrication of thin polymer/ceramic composite tapes of around 100 microns in steps, with the following technical specifications:

**Operation**: The equipment comprises of one sets of rollers having a dimension of 4" Diameter.  $\times$  8" Length. Polymer ceramic composite having 2"(L) $\times$ 2"(B)  $\times$  1mm (T) will be fed into the rollers to make tapes of size 8" (L)  $\times$  8"(B)  $\times$  100 micron (T)

# **Detailed Specifications:**

- 1. 5 HP AC motor, with suitable variable drive and in line gear box have to be provided as drive, together with direction reverse facility (BANFIGLIOLI/reputed make)
- Separate worn reduction gear box may be provided to automatically control the gap to an accuracy of 25microns by tapping the power from the 5HP motor. Safety measures have to be provided to avoid overloading of the motor. Gears/clutches for isolating the drive to control the gap between the rollers has to be provided for manual adjustment.
- 3. RPM of the rollers may be adjustable from 15 to 120. Read out of the RPM may be displayed.
- 4. Distance between the rollers may be adjustable from 5mm to 50 microns through movement of fine pitch screw rod connected to the top roller. Provision shall be provided for fixing proximity sensor, digital readout etc. to accurately measure the distance between the rollers in future.
- 5. Rollers have to be made out of hardened EN24 and the second set with hardened high carbon high chromium steel and all rollers are to be hard chrome plated and ground to 50 microns thick.
- 6. All brackets/frames have to be made out of cast iron/MS welded structure.
- 7. Gun metal bushes for roller bearing have to be provided
- 8. Suitable flanges, Timing pulleys & belt for efficient, slip free torque transmission
- 9. A suitable control panel with all the standard features for the necessary control of the machine has to be supplied.
- 10. Machine base may be fabricated up to a workable height of 3 feet with 6mm plate with required angle/channel reinforcements with powder coated finish.
- 11. Encoder, PLC and HMI/MMI suitable for digital read out of the gap between the rollers
- 12. Warranty one year from the date of installation and Commissioning

# Page 5 of 12

# (In the letter head of firm)

FORMAT OF COMPLIANCE STATEMENT OF SPECIFICATIONS (TO BE FILLED IN BY THE VENDOR WITH DOCUMENTARY EVIDENCE)

Name of the equipment: Multipass Calendaring Machine

MAKE & MODEL:

Specifications of quoted Model  one sets of rollers  8" Length. Polymer Model  (B) x 100 micron (T)  and in line gear box with direction reverse ay be provided to acy of 25microns by ety measures have to notor. Gears/clutches tween the rollers has tween the rollers has 15 to 120. Read out able from 5mm to 50 rew rod connected to 1 for fixing proximity measure the distance second omium steel and all ground to 50 microns		ואמכוווופ	MANE & MODEL:	(atta	(attach catalogue)	
ng a dimension of 4" Diameter. x 8" Length. Polymer mic composite having 2"(L)x2"(B) x 1mm (T) will be fed into mic composite having 2"(L)x2"(B) x 1mm (T) will be fed into mic composite having 2"(L)x8"(B) x 100 micron (T)  AC motor, with suitable variable drive and in line gear box be provided as drive, together with direction reverse to be provided as drive, together with direction reverse ity - (BANFIGLIOLI/reputed make)  arate worn reduction gear box may be provided to matically control the gap to an accuracy of 25microns by ling the power from the 5HP motor. Safety measures have to provided for manual adjustment. Gears/clutches solating the drive to control the gap between the rollers has be provided for manual adjustment of the gap between the rollers may be adjustable from 15 to 120. Read out the RPM may be displayed and be provided for fixing proximity of the rollers may be adjustable from 5mm to 50 ons through movement of fine pitch screw rod connected to top roller. Provision shall be provided for fixing proximity or, digital readout etc. to accurately measure the distance been the rollers in future  sor, digital readout etc. to accurately measure the distance been the rollers in future  sor, be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all rs are to be hard chrome plated and ground to 50 microns		C-MET REQUIREMENT	Specifications of quoted Model	Compliance whether "YES" OR "NO"	Deviation, if any, to be indicated in unambiguous terms	Remarks
ing a dimension of 4" Diameter, x 8" Length. Polymer amic composite having 2"(L)x2"(B) x 1mm (T) will be fed into rollers to make tapes of size 8" (L) x 3"(B) x 100 micron (T)  PAC motor, with suitable variable drive and in line gear box e to be provided as drive, together with direction reverse lity - (BANFIGLIOLI/reputed make)  arate worn reduction gear box may be provided to ormatically control the gap to an accuracy of 25microns by sing the power from the 5HP motor. Safety measures have to provided to avoid overloading of the motor. Gears/clutches isolating the drive to control the gap between the rollers has be adjustable from 15 to 120. Read out not the rollers may be adjustable from 5mm to 50 rons through movement of fine pitch screw rod connected to top roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all sers are to be hard chrome plated and ground to 50 microns k	Ö.	eration: The equipment comprises of one sets of rollers				
PAC motor, with suitable variable drive and in line gear box  P AC motor, with suitable variable drive and in line gear box  e to be provided as drive, together with direction reverse  e to be provided as drive, together with direction reverse  lity – (BANFIGLIOLI/reputed make)  arate worn reduction gear box may be provided to  matically control the gap to an accuracy of 25microns by  sing the power from the 5HP motor. Safety measures have to  provided to avoid overloading of the motor. Gears/clutches  isolating the drive to control the gap between the rollers has  be provided for manual adjustment  1 of the rollers may be adjustable from 15 to 120. Read out  he RPM may be displayed  cance between the rollers may be adjustable from 5mm to 50  cance between the rollers may be adjustable from 5mm to 50  construction shall be provided for fixing proximity  sor, digital readout etc. to accurately measure the distance  ween the rollers in future  ers have to be made out of hardened EN24 and the second  with hardened high carbon high chromium steel and all  ers are to be hard chrome plated and ground to 50 microns  k	hav	a dimension of 4" Diameter. x 8" composite baying 2"(1)<2"(B) x 1mm (1)				
P AC motor, with suitable variable drive and in line gear box e to be provided as drive, together with direction reverse lity – (BANFIGLIOLI/reputed make)  arate worn reduction gear box may be provided to omatically control the gap to an accuracy of 25microns by ping the power from the 5HP motor. Safety measures have to provided to avoid overloading of the motor. Gears/clutches isolating the drive to control the gap between the rollers has be provided for manual adjustment 1 of the rollers may be adjustable from 15 to 120. Read out he RPM may be displayed rance between the rollers may be adjustable from 5mm to 50 rans through movement of fine pitch screw rod connected to top roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	the	reflect to make tapes of size $8''(L) \times 8''(B) \times 100$ micron (T)				
e to be provided as drive, together with direction reverse lity – (BANFIGLIOLI/reputed make)  Jarate worn reduction gear box may be provided to comatically control the gap to an accuracy of 25microns by ping the power from the 5HP motor. Safety measures have to provided to avoid overloading of the motor. Gears/clutches isolating the drive to control the gap between the rollers has be provided for manual adjustment  1 of the rollers may be adjustable from 15 to 120. Read out he RPM may be displayed tance between the rollers may be adjustable from 5mm to 50 rons through movement of fine pitch screw rod connected to top roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future lers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns is	5 H	IP AC motor, with suitable variable drive and in line gear box				
Jarate worn reduction gear box may be provided to comatically control the gap to an accuracy of 25microns by ping the power from the 5HP motor. Safety measures have to provided to avoid overloading of the motor. Gears/clutches isolating the drive to control the gap between the rollers has be provided for manual adjustment.  1 of the rollers may be adjustable from 15 to 120. Read out he RPM may be displayed cance between the rollers may be adjustable from 5mm to 50 cance between the rollers may be adjustable from 5mm to 50 consected to to rons through movement of fine pitch screw rod connected to to to accurately measure the distance ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	hav faci	re to be provided as drive, together with direction reverse lity – (BANFIGLIOLI/reputed make)				
omatically control the gap to an accuracy of 25microns by ping the power from the 5HP motor. Safety measures have to provided to avoid overloading of the motor. Gears/clutches isolating the drive to control the gap between the rollers has be provided for manual adjustment.  1 of the rollers may be adjustable from 15 to 120. Read out he RPM may be displayed cance between the rollers may be adjustable from 5mm to 50 rons through movement of fine pitch screw rod connected to top roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	Sep	worn reduction gear box may be provided				
ping the power from the 5HP motor. Safety measures have to provided to avoid overloading of the motor. Gears/clutches isolating the drive to control the gap between the rollers has be provided for manual adjustment.  I of the rollers may be adjustable from 15 to 120. Read out he RPM may be displayed cance between the rollers may be adjustable from 5mm to 50 rons through movement of fine pitch screw rod connected to top roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	aut	of 25microns				
provided to avoid overloading of the motor. Gears/clutches isolating the drive to control the gap between the rollers has be provided for manual adjustment.  I of the rollers may be adjustable from 15 to 120. Read out he RPM may be displayed and be adjustable from 5mm to 50 and the rollers may be adjustable from 5mm to 50 and the roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future are have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all are sare to be hard chrome plated and ground to 50 microns k	tap	oing the power from the 5HP motor. Safety measures have to				
isolating the drive to control the gap between the rollers has be provided for manual adjustment.  1 of the rollers may be adjustable from 15 to 120. Read out he RPM may be displayed and be adjustable from 5mm to 50 and the rollers may be adjustable from 5mm to 50 and the roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future are have to be made out of hardened EN24 and the second with hardened high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	þe	provided to avoid overloading of the motor. Gears/clutches				
le provided for manual adjustment  1 of the rollers may be adjustable from 15 to 120. Read out he RPM may be displayed leance between the rollers may be adjustable from 5mm to 50 leance between the rollers may be adjustable from 5mm to 50 leance between the rollers may be adjustable from 5mm to 50 leance between the rollers may be adjustable from 5mm to 50 leance between the rollers may be adjustable from 5mm to 50 leance between the rollers in future leance he made out of hardened EN24 and the second leance with hardened high carbon high chromium steel and all leance be hard chrome plated and ground to 50 microns leance between to be hard chrome plated and ground to 50 microns	for	isolating the drive to control the gap between the rollers has				
he RPM may be adjustable from 15 to 120. Read out he RPM may be displayed cance between the rollers may be adjustable from 5mm to 50 rons through movement of fine pitch screw rod connected to top roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns	엄	e provided for manual adjustment				
he RPM may be displayed  tance between the rollers may be adjustable from 5mm to 50  rons through movement of fine pitch screw rod connected to  top roller. Provision shall be provided for fixing proximity  sor, digital readout etc. to accurately measure the distance  ween the rollers in future  lers have to be made out of hardened EN24 and the second  with hardened high carbon high chromium steel and all  ers are to be hard chrome plated and ground to 50 microns  k	RP	1 of the rollers may be adjustable from 15 to 120. Read out				
rance between the rollers may be adjustable from 5mm to 50 rons through movement of fine pitch screw rod connected to top roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	oft	he RPM may be displayed				
tons through movement of fine pitch screw rod connected to to to shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future lers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns	Dis	tance between the rollers may be adjustable from 5mm to 50				
top roller. Provision shall be provided for fixing proximity sor, digital readout etc. to accurately measure the distance ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	T Sign	rons through movement of fine pitch screw rod connected to				
sor, digital readout etc. to accurately measure the distance  ween the rollers in future  ers have to be made out of hardened EN24 and the second  with hardened high carbon high chromium steel and all  ers are to be hard chrome plated and ground to 50 microns  k	the	top roller. Provision shall be provided for fixing proximity				
ween the rollers in future ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	sen	sor, digital readout etc. to accurately measure the distance				
ers have to be made out of hardened EN24 and the second with hardened high carbon high chromium steel and all are to be hard chrome plated and ground to 50 microns k	bet	ween the rollers in future				
with hardened high carbon high chromium steel and all ers are to be hard chrome plated and ground to 50 microns k	Roll	ers have to be made out of hardened EN24 and the second				
ers are to be hard chrome plated and ground to 50 microns	set	with hardened high carbon high chromium steel and all				
×	<u>e</u> :	ers are to be hard chrome plated and ground to 50 microns				
	thic	<b>Y</b>				

S No	C-MET REQUIREMENT	Specifications of quoted Model	Compliance whether "YES" OR "NO"	Deviation, if any, to be indicated in unambiguous terms	Remarks
7.	All brackets/frames have to be made out of cast iron/MS welded structure				
œ.	Gun metal bushes for roller bearing have to be provided				
9.	Suitable flanges, Timing pulleys & belt for efficient, slip free torque transmission				
10.	A suitable control panel with all the standard features for the necessary control of the machine has to be supplied				
11.	Machine base may be fabricated up to a workable height of 3 feet with 6mm plate with required angle/channel reinforcements with powder coated finish				
12.	Encoder, PLC and HMI/MMI suitable for digital read out of the gap between the rollers				
13.	Warranty – one year from the date of installation and Commissioning				

Signature of Tenderer	Name	Seal of the tenderer

# (in the company letter head)

# **BID FORM AND PRICE SCHEDULE**

Tender Reference No. : ENQ. NO.: $HD/POR/SP-39/MCM/10/2019-20/1/A$	Tender Reference No.		ENQ. NO.: HD/PUR/SP-39/MCM/10/2019-20/1146
--	----------------------	--	--

Date : 13.12.2019

Name of the Stores/

Goods/Equipment : Multipass Calendaring Machine

SI. No.	Description	Qty	HSN CODE	Rate/Rs.	Amount/Rs.
1	Multipass Calendaring Machine	1 no.			
	GST				
	Freight Charges				
	Packing & Forwarding				
	Transit Insurance				
	TOTAL				

	_	
1	Payment Ter	mc.
1.4	rayillelit lei	1115.

- 2. Bid Validity:
- 3. Delivery Schedule:
- 4. Place of delivery:
- 5. Warranty, if applicable:
- 6. GST Registration No.:
- 7. Any other relevant information:

Signature of Tenderer	: <del></del>
Name	
Seal of the tenderer	

# (in the company letter head)

# **BIDDER'S DETAILS**

1	Name of the supplied/party/firm	
2	Name of the authorized representative	
3	Communication address	
4	Telephone Nos	
5	Mobile Nos	
6	Fax and e-mail address	
7	Web address	
8	Bank details for payment through NEFT/RTGS	
9	Name of Bank	
	Branch	
	Account No	
	IFSC No	
	MICR No	
	Cancelled cheque for verification of above details	

(Signature & seal of the bidder)

# (in the company letter head)

# PRICE REASONABILITY CERTIFICATE

It is certified that	the rates quoted		are	not more t	han
as charged to other Gov	vt. /PSU's for simila	r supplies made	in recent p	ast. Copie	s of
the supply orders rec	eived from other	Govt/PSU's are	enclosed	alongwith	the
technical bid.					
	Signature	of Tenderer			
	o.g.i.acai o				
	Busir	ness Address			
	Seal of th	—— ne Tenderer			

# (TO BE SUBMITTED ALONG WITH TECHNICAL BID)

# (in the company letter head)

To.

. • /		
The Administrative Officer C-MET, IDA Phase III Cherlapally, Hyderabad 500 051	Date:	
Sub: Acceptance of Terms & Conditions of Ter	nder.	
Tender Reference No.	dated	
Name of the Tender/Work:		
Sir/Madam,		
I/We have downloaded/obtained the tender document(s) for the above mentioned `Tender/Work' for the web site(s) namely:		
as per your advertisement, given in the mentioned website(s)/enquiry letter.  2. I/we hereby certify that I/we have read the entire terms & conditions of the tender documents from Page No to (including all documents like Annexure(s), schedules(s), etc.) which form part of the contract agreement and I/We shall abide hereby by the terms/conditions/clauses contained therein.		
3. The corrigendum(s) issued from department/organization too have all bees submitting this acceptance letter.		
4. I/We hereby unconditionally accept mentioned tender document (s)/Corrigendum		
5. In case any provisos of this tender Department/Organizations shall without prejuted at liberty to reject this tender/bid including the money deposit absolutely.	dice to any other right or remedy be	
	Yours faithfully,	

Page 10 of 12

Name & Signature of the Supplier/Contractor/ Authorized signatory with Official stamp/seal

# (TO BE SUBMITTED ALONG WITH TECHNICAL BID)

# (in the company letter head)

# **UNDERTAKING/ DECLARATION**

I/We having our office at declare that I/we
have never been blacklisted by any State Government/Central Government or any State/Central PSU.
2. I/We, hereby declare that the particulars furnished by me/us in this offer are true to the best of my/our knowledge and I/We understand and accept that, if at any stage the information furnished by me/us are found to be incorrect or false, I/We am/are liable for disqualification from this tender and also liable for any penal action that may arise due to the above, besides being black listed.
3. I/We hereby accept to provide Warranty/Guarantee, additional Warranty, Comprehensive AMC
4. This is also certified that the rates quoted in the financial bid are not more than the rates charged from any other Institution/Department/Organization in the last six months. No Other charges would be payable by the Institute.
have gone through the terms and conditions and will abide by them as laid down above. I hereby undertake that the information provided above and elsewhere in the tender is true and the tender is liable to rejection if the same is found to be false or the information is found to have been suppressed by me.
Name & Signature of the Supplier/Contractor/ Authorized signatory with Official stamp/seal

# (NOTE: WITHOUT THIS BID WILL BE REJECT - TO BE SUBMITTED ALONGWITH TECHNICAL BID) (in the company letter head)

# **MANUFACTURER'S AUTHORISATION FORM**

The Administrative Officer C-MET, IDA Phase-III Cherlapally, HCL Post Hyderabad – 500 051 TELANGANA STATE, India

Dear Sir,
Ref. Your TE document No, dated
We, who are proven and reputable manufacturers of (name and description of the goods offered in the tender) having factories at
hereby authorize Messrs
We further confirm that no supplier or firm or individual other than Messrs. (name and address of the above agent) is authorized to submit a tender, process the same further and enter into a contract with you against your requirement as contained in the above referred TE documents for the above goods manufactured by us.
We also hereby extend our full warranty as applicable as per tender clause for the goods and services offered for supply by the above firm against this TE document.
We also hereby confirm that we would be responsible for the satisfactory execution of contract placed on the authorized agent.
We also confirm that the price quoted by our agent shall not exceed than that which we would have quoted directly.
Yours faithfully,
[Signature with date, name and designation] For and on behalf of Messrs

[Name & address of the manufacturers]

Note: 1. This letter of authorization should be on the letterhead of the manufacturing firm and should be signed by a person competent and having the power of attorney to legally bind the manufacturer.

2. Original letter may be sent.